



၁။ ဥပဒေရေးရာဝန်ကြီးဌာန၏ ၂၀၂၆-၂၀၂၇ ခု၊ ဘဏ္ဍာနှစ် ငွေလုံးငွေရင်း (စက်ပစ္စည်း) အသုံးစရိတ်ခွင့်ပြုရန်ပုံငွေမှ ဥပဒေအသိပညာပြန့်ပွားရေး သင်တန်းကျောင်း၊ နေပြည်တော်တွင် အသုံးပြုရန် ရေသန့်စက် (Water Purification System) ဝယ်ယူတပ်ဆင်ခြင်း ဆောင်ရွက်ရန်အတွက် အိတ်ဖွင့်တင်ဒါ ဈေးနှုန်းများခေါ်ယူရန် ဖိတ်ခေါ်အပ်ပါသည်-

စဉ် လုပ်ငန်းအမျိုးအမည်

၁။ ရေသန့်စက် (Water Purification System) ဝယ်ယူ တပ်ဆင်ခြင်း 1 Set

၂။ အိတ်ဖွင့်တင်ဒါနှင့် ပတ်သက်သည့် အောက်ဖော်ပြပါ အချက်အလက်များကို (၂၃.၇.၂၀၂၆) ရက်နေ့မှစ၍ ဥပဒေရေးရာဝန်ကြီးဌာန၊ ဥပဒေအသိပညာပြန့်ပွားရေးဦးစီးဌာန၊ ကြီးကြပ်စီမံဌာနခွဲ ၊ ရုံးအမှတ်- ၂၅ တွင် စတင်ဝယ်ယူနိုင်ပါသည်-

- (က) အိတ်ဖွင့်တင်ဒါပုံစံ၊
- (ခ) တင်ဒါစည်းမျဉ်းစည်းကမ်းများနှင့်
- (ဂ) အသေးစိတ်အချက်အလက်များ Request for Proposal

၃။ အိတ်ဖွင့်တင်ဒါများကို (. ၇ . ၈ . ၂၀၂၆) ရက်နေ့ (၁၆:၀၀) နာရီ နောက်ဆုံးထား၍ ဥပဒေရေးရာ ဝန်ကြီးဌာန၊ ဥပဒေအသိပညာပြန့်ပွားရေးဦးစီးဌာန၊ ကြီးကြပ်စီမံဌာနခွဲ ၊ ရုံးအမှတ်- ၂၅ သို့ တင်သွင်း ပေးပို့ ရန်ဖြစ်ပါသည်။

၄။ အိတ်ဖွင့်တင်ဒါနှင့် ပတ်သက်သော အသေးစိတ်အချက်အလက်များကို အောက်ပါ လိပ်စာနှင့် ဖုန်းနံပါတ်များသို့ စုံစမ်းမေးမြန်းနိုင်ပါသည်။

တင်ဒါကော်မတီ

ဥပဒေရေးရာဝန်ကြီးဌာန

ရုံးအမှတ် (၂၅) ၊ နေပြည်တော်

ဖုန်း- ၀၉-၄၀၅၅၆၀၅

အသေးစိတ်အချက်အလက်များ Request for Proposal

ရေသန့်စနစ် (Water Purification System) ဝယ်ယူတပ်ဆင်ခြင်း

-

1 Set

(1) AUTO PRESSURE PUMP

A. TYPE : KBK BWJ 2-4

B. Q max: 2 m³/hr

(2) SAND FILTER

Material : FRP

Max Pressure : 150 psi

Max Temperature : 49 C

Max Temperature : 1 C

Type : Vertical with control valve frame, diffusers, strainer
& pressure gauge

Dimension : Ø13" x 54" H

Filter Media : PURIFIED &STERILIZED SILICA SAND, Gravel

Volume : SAND 60 Liter, ½"×¼"
Gravel 20 liter

(3) GAC FILTER

Material : FRP

Max Pressure : 150 psi

Max Temperature : 49 C

Max Temperature : 1 C

Type : Vertical with control valve frame, diffusers, strainer &
pressure gauge

Dimension : Ø13" x 54" H

Filter Media : GRANULAR ACTIVATED CARBON(USA), Gravel

Volume : CARBON 60 Liter, ½"×¼" Gravel 20 liters

(4) REGENERATION SYSTEM

Including : - Ejector
- Regeneration Tank

Origin : Thailand

(5) SOFTENER

Material : FRP

Max Pressure : 150 psi
Max Temperature : 49 C
Max Temperature : 1 C
Type : Vertical with control valve frame, diffusers, strainer & pressure gauge
Dimension : Ø13" x 54" H
Filter Media : RESIN(USA), Gravel
Volume : RESIN 60 Liter, ½" x ¼"
Gravel 20 liter

(6) Reverse Osmosis Drinking Water Treatment System

- Capacity : 2000 GPD
1. RO Membrane (FILMTEC BW 30-4040)
 2. Housing : FRP
 3. Pump : TYP-2507, 1 HP, 1 Phase
 4. Absolute Filter 5 Micron x 20" Height 2 Sets
 5. Control Function;
 - a. Low Pressure Switch Prevent no Feed Water
 - b. Feed Water Solenoid Valve
 - c. Pump Pressure Regulator
 - d. Drain Water Regulator
 - e. Product Water Flow Meter
 - f. Drain Water Flow Meter
 - g. System Control Monitor
 - h. TDS Meter
 - i. Auto Flush with Timer
- Auto Float Switch

(7) STEEL TANK (1000 Liter) with Leg

(8) PIPING AND FITTING

INSTALLATION AND SUPERVISION.